

QUOTE REQUEST FORM

This form is the first step to creating your customized Bally Walk-In Cooler/Freezer with up to 3 compartments. (If your Walk-In requires more than 3 compartments, you do not need to fill out the form just email us or call 1-800-24BALLY.) Please fill out this form, adding any comments or questions, and email it to sales@ballyrefboxes.com.

A Bally representative will contact you with information and help you find a dealer in your area.

A Bany representative will co	ntact you with infor	таноп апа петр уог	u iiria a aeaier iri your	area.		
Name:		Email:				
Business Name:		Project Name:				
Address:		City: State Zip				
Phone:		Fax:				
OVERALL DIMENSI	ONS of W	ALK-IN 🗆	4″ Panel ☐ 5″ Pane	el □6″Panel		
Estimated LENGTH:	Estimated WIDTH:	Estimated HEIGHT:				
*Choose from: 5'10", 6'3¾", 6'9½", 7'3¼", 7'9", 8'2¾", 8'8½", 9'2¼", 9'8", 10'1¾", 10'7½", 11'1¼", 11'7", 12'0¾", 12'6½", 13'0¼", 13'6", 14'5½", 15'5", 16'4½", 17'4", 18'3½", 19'3", 20'2½". Longer buildings are available in additional 5¾" increments.	*Choose from: 6'6", 7'6", 8'6", 9'6", 10'6", 9'2¼", 9'8", 10'1¾", (Single length verticals) 11'7", 12'0¾", 12'6½", Taller buildings are available in additional 11½" els. Heights shown are with floor; subtract 4" for less-floor units.					
*Non-Standard dimensions can expect longer lead times.						
Number of Compartments? (Check one)	ndoor: On Grade or Depression Outdoor: Free Standing		Height of Building (if against one):			
□ 1 □ 2 □ 3 Other Inst			Number of Walls Size x			
H	Dimensions: Cooler: Lx Wx Freezer: Lx Wx		Hand sketch of the coole	r/freezer		
Comments:						
Exterior Finish: (Check one) Stucco-embossed Galvalume steel Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White aluminum Stucco-embossed Sand-tan galvanized steel Stucco-embossed White galvanized steel Sandex Stone-textured Galvanized steel Embossed Stainless		☐ Stucco-emb ☐ Smooth Wh ☐ Stainless ste ☐ Stucco-emb ☐ Stucco-emb ☐ Stucco-emb ☐ Smooth Wh	Interior Finish: (Check one) Stucco-embossed Galvalume steel Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White aluminum Stucco-embossed White galvanized steel Smooth White aluminum Embossed Stainless			

FLOORS		Floor Types: (Check one) Less Floor w/ Floor w/ Floor—Less Floor Light Use—Foot Traffic Medium Use—Hand Truck or Small Cart Heavy Duty—Structurally Reinforced (Keg or Pallet Jack & Queen Mary)			Floor Panel Finishes: (Check one) 3/16" Aluminum Diamond Tread Overlay 100 ga. Smooth Aluminum 16 ga. Stainless Steel Rigidized Aluminum Diamond Pattern 1/8" Aluminum Diamond Tread Rigidized Stainless Steel Diamond Pattern 16 ga. Galvanized Steel (Non NSF - to be used under any NSF approved Overlay) Extra Overlay: 3/16" Diamond Tread				
			FS - Options: <i>(Check one)</i> ane roof w/ tapered insulation						
	Door 1			Door Options: Observation Window in Entrance Door: 14" x 14" Deadbolt Handle Latch: (K27C) Strip Curtain(s)					
OORS	Door 2	Width: Choose from: 30", 36", 42", 48", 54", 60"	Height: Choose from: 66", 78", 84"			Super Doors (1/8" Diamondtread kickplate on both sides, 3"d hinge. Standard Sizes; included unless noted)			
	Door 3	Width: Choose from: 30", 36", 42", 48", 54", 60"	Hei	Height: Choose from: 66", 78", 84"		Glass Display Doors: Number of Doors: Size: x			
	Ad	Additional Doors:		☐ Sliding Door: Qty Size: x Slide Direction: ☐ Left ☐ Right					
				ACCE	SS	ORIES			
☐ Pressure Relief Port (required for freezers) Additiona ☐ Partition Walls (location) ☐ Yes ☐ Free Standing Shelving If yes: ☐			al Lighting: No 4'LED Other		Alarm Systems: Modularm 75L C WEISS Other: Please specify				
	R	EFRIGERAT	10	N SYS	TE	MS □Sto	rage	Only Product Load	
nt 1	Conde Conde Ir O	ation (Choose one): ooler Freezer nsing Unit: ndoor Remote outdoor Air-Cooled Remot elf-Contained (PT-Unit)		Condensii Indo Outo	er [ng Un oor Re door <i>A</i> Conta	Freezer	Compartment 3	Application (Choose one): Cooler Freezer Condensing Unit: Indoor Remote Outdoor Air-Cooled Remote Self-Contained (PT-Unit)	

Notes: For line sets ≤ 75'

 ${\it SmartVap+Evaporator\ Controls\ are\ Standard\ at\ Bally}.$